Total number of printed pages-4

53 (CD 801) DGST

ENTRAL INSTITU

2019

## **DESIGN OF STRUCTURES-III**

Paper: CE 801

Full Marks: 100

Time: Three hours

The figures in the margin indicate full marks for the questions.

Answer any five questions.

1. (a) Define Pre-stressed concrete and discuss the advantages & disadvantages of Pre-stressed concrete.

stricts of steel-with the following

6

Contd.

- at mid-section without the action of live load
- (ii) live load at mid-section with the action of
- (iii) at end-section with the action of
- (a) List out the various losses in pre-stressed concrete and explain any and one in detail.

  1 pre-tensioned to

2

(b) deformation, creep, shrinkage and of loss of stress due to elastic initially stressed to 1200N/mm2 and 350mm deep is pre-stressed by relaxation of steel with the following with their centroid locator at 100mm from the soffit. Calculate the final % 15 number of wires of 6mm dia,

data:

shrinkage strain  $= 3 \times 10^{-4}$ Creep coefficient  $(\phi) = 1.6$  Residual

$$E_{\rm s} = 210 kN / m^2$$
,  
 $E_{\rm c} = 35 kN / m^2$ 


$$E_c = 35kN/m^2$$

14

ယ Floor finish =  $1.0kN/m^2$ . width of flight = 1.2m, live load =  $4kN/m^2$ . for the following data. Floor height = 3.2mDesign a dog-legged stai for an office building

exposure condition. concrete and Fe 500 steel. Assume mild the landing parallel to the risers. Use M25 Assume the stair to be supported on 230mm thick masonry walls at the outer edges of

SHAME INSTITUTE OF Analyze the frame shown in fig-1 by cantilever method. Also draw the B.M.D. & S.F.D.



0

- 5. Design a rectangular water tank resting on ground for a capacity of 75000 litres. Use M30 concrete and Fe 500 steel.
- 6. Design a foot-bridge for the following data: 20
  - (a) Span of girder 12m c/c
  - (b) Cross girder spacing 2.5m c/c
  - (c) Clear working width between main girder 3.0m
  - (d) Live load  $5.0kN/m^2$
  - (e) Flooring timber plank
    Assume any missing data.

